


# CC1A-T1AH

## SM Crystal -55+200°C


- Suitable for Avionics, Down-hole, Geothermal etc
- Extreme temperature ranges up to 200°C
- High stability & low ageing under extremes
- High shock & vibration resistance
- Ultra low MSL



### CONFIGURABLE OPTIONS

Parameter	Option Code
-----------	-------------

## PACKAGE DRAWING



## ORDERING INFORMATION

To request a quotation for the CC1A-T1AH please use the configurable options form to choose the options you require and then submit your configured product to our team. Our expert advisers are always happy to help with your requirements and can be contacted on +44 1460 256 100 or at [sales@golledge.com](mailto:sales@golledge.com).

Following product selection you will be issued with a seven character Golledge part number. Your Golledge part number is the internationally accepted Golledge manufacturing part number (MPN) that should be used for all project documentation, including bills of materials (BoMs) and purchase orders.

If you have any queries regarding any of our documentation our dedicated sales team will be happy to help.

### Order now from Digikey


Order now from [Digikey](#)

**ORDER NOW FROM DIGIKEY**

**DigiKey Buy now**

**DigiKey Buy now**

## TAPE & REEL SPECIFICATION



A:178\* B:16 C:8.5 D:4.4 E:8 F:2 G:80 H:21

\*Larger reel size available. Please ask for details

## CONSTRUCTION

Ceramic base and lid

## HANDLING & STORAGE



Human Body Model (HBM) 1A (250V to < 500V)



Moisture Sensitivity Level (MSL): 1

## COMPLIANCE



Lead-free (< 0.1% by weight )



RoHS compliant with no exemptions.