

GMCF-HF 70G15A

70MHz 2 pole crystal filter with
15.0kHz 3dB bandwidth

- Standard models available from stock
- Custom specifications available



CONFIGURABLE OPTIONS

Parameter	Option Code
-----------	-------------



SPECIFICATIONS

Centre frequency	70.0MHz
Dimensions	Package options available - see Package Drawing
Operating temperature range	-20 to +70 °C
Number of poles	2
Pass band	-3dB @ $\pm 7.5\text{kHz}$ min
Attenuation band	-15dB @ $\pm 30.0\text{kHz}$ max
In-band ripple	1.0dB max
Insertion loss	2.0dB max
Guaranteed attenuation	-35dB max +500 ~ +1000kHz -35dB max -200 ~ -1000kHz
Termination	2000 Ω // -1.0pF
Package style	UM-1/3L, UM-5/3L (through-hole) UM-1JN/3L, UM-5JN/3L (SMT)

PACKAGE DRAWING


Package Options

Through hole



Package	Height H
UM-1/3L	8.00 max
UM-5/3L	6.00 max

Surface mounted



Package	Length L
UM-1JN/3L	12.50 max
UM-5JN/3L	10.50 max

Dimensions in mm

ORDERING INFORMATION

To request a quotation for the GMCF-HF 70G15A please use the configurable options form to choose the options you require and then submit your configured product to our team. Our expert advisers are always happy to help with your requirements and can be contacted on +44 1460 256 100 or at sales@golledge.com.

Following product selection you will be issued with a seven character Golledge part number. Your Golledge part number is the internationally accepted Golledge manufacturing part number (MPN) that should be used for all project documentation, including bills of materials (BoMs) and purchase orders.

If you have any queries regarding any of our documentation our dedicated sales team will be happy to help.

CONSTRUCTION

Resistance weld

HANDLING & STORAGE



Human Body Model (HBM) 1A (250V to < 500V)



Moisture Sensitivity Level (MSL): 1

COMPLIANCE
