

# GVXO-43H

## 3.3V VCXO

- Low cost for volume applications
- Choice of pullability & stability
- Express deliveries for non-standard items
- Industrial temperature range option




### CONFIGURABLE OPTIONS

Parameter	Option Code
Frequency	
Frequency pullability	
Any	
±50ppm min	N
±100ppm min	S
±150ppm min	W
Frequency stability	
Any	
±100ppm max	A
±50ppm max	B
±25ppm max	C
±20ppm max	D
±15ppm max	E
Operating temperature range	
Any	
-10 to +70 °C	
-40 to +85 °C	I



## SPECIFICATIONS

Frequency range	1.544 ~ 30.0MHz
Dimensions	13.08 x 13.08 x 5.70mm
Package	8 pin DIL (half size)
Voltage control	+1.65V $\pm$ 1.65V, 10% linearity > 100k $\Omega$ input impedance
Ageing	$\pm$ 5.0ppm max per year
Storage temperature range	-55 to +125 °C
Supply voltage (V <sub>DD</sub> )	+3.3V ( $\pm$ 5%)
Supply current	10mA max (<20.0MHz) 15mA max (20.0 ~ 33.0MHz)
Driving ability	30pF HCMOS 5 LSTTL
Logic levels	'0' level = +0.4V max '1' level = 90%V <sub>DD</sub> min
Waveform symmetry @ 50%V <sub>DD</sub>	40:60 max
Rise / fall time	5ns max (0.4V ~ 90%V <sub>DD</sub> min)

## PACKAGE DRAWING



PIN	CONNECTION
1	Control voltage
4	Ground
5	Output
8	Supply



Dimensions in mm

## ORDERING INFORMATION

To request a quotation for the GVXO-43H please use the configurable options form to choose the options you require and then submit your configured product to our team. Our expert advisers are always happy to help with your requirements and can be contacted on +44 1460 256 100 or at [sales@golledge.com](mailto:sales@golledge.com).

Following product selection you will be issued with a seven character Golledge part number. Your Golledge part number is the internationally accepted Golledge manufacturing part number (MPN) that should be used for all project documentation, including bills of materials (BoMs) and purchase orders.

If you have any queries regarding any of our documentation our dedicated sales team will be happy to help.

## HANDLING & STORAGE



Human Body Model (HBM) 1A (250V to < 500V)



Moisture Sensitivity Level (MSL): 1

## CONSTRUCTION

---

Resistance weld

## COMPLIANCE

---



Lead-free (< 0.1% by weight )



RoHS compliant with no exemptions.